

SABIC Innovative Plastics LNP Thermotuf PK005EI2 PA 6 (Europe-Africa-Middle East)

Category : Polymer , Thermoplastic , Nylon , Nylon 6

Material Notes:

LNP* THERMOTUF* PK005EI2 is a compound based on PA 6 resin containing Impact Modifier, Mineral. Added features include: High Impact. This data was supplied by SABIC-IP for the Europe-Africa-Middle East region.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-Thermotuf-PK005EI2-PA-6-Europe-Africa-Middle-East.php

Physical Properties	Metric	English	Comments
Density	1.31 g/cc	0.0473 lb/in ³	ISO 1183
Linear Mold Shrinkage, Flow	0.0060 - 0.0080 cm/cm	0.0060 - 0.0080 in/in	SABIC Method

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	55.0 MPa	7980 psi	5 mm/min; ISO 527
Elongation at Break	>= 8.0 %	>= 8.0 %	5 mm/min; ISO 527
Flexural Yield Strength	70.0 MPa	10200 psi	2 mm/min; ISO 178
Flexural Modulus	3.60 GPa	522 ksi	2 mm/min; ISO 178
Izod Impact, Notched (ISO)	8.00 kJ/m ² @Temperature 23.0 °C	3.81 ft-lb/in ² @Temperature 73.4 °F	80*10*4; ISO 180/1A
Izod Impact, Unnotched (ISO)	70.0 kJ/m ² @Temperature 23.0 °C	33.3 ft-lb/in ² @Temperature 73.4 °F	80*10*4; ISO 180/1U

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	56.0 °C	133 °F	Flatw 80*10*4 sp=64mm; ISO 75/Af

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China