

SCG Chemicals EL-Leneâ„¸ H5211PBL High Density Polyethylene Pipe Resin

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Pipe Grade

Material Notes:

Key Characteristics: Good processing, high thermal stability, good resistance to weathering
 Recommended Applications: Stripe lines for PE80 pipe, non pressure pipes
 Certification: Certified by LNE
 Information provided by SCG Chemicals

Order this product through the following link:

http://www.lookpolymers.com/polymer_SCG-Chemicals-EL-Lene-H5211PBL-High-Density-Polyethylene-Pipe-Resin.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.956 g/cc	0.956 g/cc	ISO 1183
Environmental Stress Crack Resistance	>= 10000 hour	>= 10000 hour	F0; ASTM D1693
Oxidative Induction Time (OIT)	>= 20 min @Temperature 200 Â°C	>= 20 min @Temperature 392 Â°F	ISO/TR10837
Melt Flow	0.44 g/10 min @Load 5.00 kg, Temperature 190 Â°C	0.44 g/10 min @Load 11.0 lb, Temperature 374 Â°F	ISO 1133

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	64	64	ASTM D2240
Tensile Strength at Break	35.0 MPa	5080 psi	Crosshead speed 100 mm/min; ISO 527
Tensile Strength, Yield	25.0 MPa	3630 psi	Crosshead speed 100 mm/min; ISO 527
Elongation at Break	860 %	860 %	Crosshead speed 100 mm/min; ISO 527
Flexural Modulus	1.08 GPa	157 ksi	ASTM D790
Izod Impact, Notched	1.74 J/cm @Temperature 23.0 Â°C	3.25 ft-lb/in @Temperature 73.4 Â°F	ASTM D256

Thermal Properties	Metric	English	Comments
Brittleness Temperature	<= -60.0 Â°C	<= -76.0 Â°F	ASTM D746

Descriptive Properties	Value	Comments
Carbon Black/Pigment Dispersion (grade)	<3	ISO 18553
Color	Blue	RAL5012

Descriptive Properties	Value	Comments
------------------------	-------	----------

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China