

## S&E Specialty Polymers GPP™ 1005M-EXLT PP

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Flame Retardant

**Material Notes:**

Application: UL94 V-2, Non-blooming flame retardant polypropylene compound for injection molding. Information provided by S&E Specialty Polymers

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_SE-Specialty-Polymers-GPP-1005M-EXLT-PP.php](http://www.lookpolymers.com/polymer_SE-Specialty-Polymers-GPP-1005M-EXLT-PP.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.940 - 0.960 g/cc	0.940 - 0.960 g/cc	ASTM D792
Melt Flow	12 - 16 g/10 min	12 - 16 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	>= 23.4 MPa	>= 3400 psi	ASTM D638
Elongation at Break	>= 120 %	>= 120 %	ASTM D638
Flexural Modulus	>= 1.38 GPa	>= 200 ksi	ASTM D790
Izod Impact, Notched	>= 1.12 J/cm	>= 2.10 ft-lb/in	ASTM D256
Gardner Impact	>= 260 J @Thickness 3.17 mm	>= 192 ft-lb @Thickness 0.125 in	ASTM D5420

Thermal Properties	Metric	English	Comments
Flammability Test	3.0 @Thickness 1.59 mm	3.0 @Thickness 0.0625 in	
Oxygen Index	>= 24 %	>= 24 %	ASTM D2863

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China