

S&E Specialty Polymers TufTech™ GA-1052-55 PVC Compound

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

Application: A 105°C scuff, oil and flame resistant high flow molding compound designed for grommets. Information provided by S&E Specialty Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_SE-Specialty-Polymers-TufTech-GA-1052-55-PVC-Compound.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.35 g/cc	1.35 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	55.0	55.0	ASTM D2240
	@Time 15.0 sec	@Time 0.00417 hour	
Tensile Strength	>= 6.89 MPa	>= 999 psi	ASTM D412
Elongation at Break	>= 400 %	>= 400 %	ASTM D412
100% Modulus	0.00207 GPa	0.300 ksi	ASTM D412

Processing Properties	Metric	English	Comments
Processing Temperature	171 - 182 °C	340 - 360 °F	Suggested Stock

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China