

S&E Specialty Polymers XP110-13-45 PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Uncompounded

Material Notes:

Description: PVC weatherable, integral colored, filledApplication: Body side end cap extrusion and injection molding compound designed for anti-stain which meets GMP.PVC.093, GMP.PVC.094 & Chrysler MSDC 543Information provided by S&E Specialty Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_SE-Specialty-Polymers-XP110-13-45-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	<= 1.40 g/cc	<= 1.40 g/cc	ISO 1183, A

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	42 - 48	42 - 48	ISO 868
	@Time 15.0 sec	@Time 0.00417 hour	
Tensile Strength	>= 15.0 MPa	>= 2180 psi	Type IV, 500mm/min; ISO 37
Elongation at Break	>= 150 %	>= 150 %	Type IV, 500mm/min; ISO 37

Descriptive Properties	Value	Comments
Accelerated Weathering	<3.0 DE	after 2000 kj/m ² , SAEJ2527
Cold Flex	-30°C	GM9503P

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China