

## SGL Carbon Group PANOX® FA T320 EEA High performance oxidized textile fiber, Continuous Tow with 320k filaments

Category : Carbon , Carbon Fiber , Other Engineering Material , Composite Fibers

### Material Notes:

For carbon/carbon and spinning. PANOX® is the industry standard when it comes to fire-retardant textile fibers. As an oxidized, thermally stabilized polyacrylonitrile (PAN) fiber that will not burn, melt, soften or drip, PANOX is ideal for processing into yarns, woven fabrics, nonwovens and felts. Information provided by SGL Carbon Group

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_SGL-Carbon-Group-PANOX-FA-T320-EEA-High-performance-oxidized-textile-fiber-Continuous-Tow-with-320k-filaments.php](http://www.lookpolymers.com/polymer_SGL-Carbon-Group-PANOX-FA-T320-EEA-High-performance-oxidized-textile-fiber-Continuous-Tow-with-320k-filaments.php)

Physical Properties	Metric	English	Comments
Density	1.39 - 1.43 g/cc	0.0502 - 0.0517 lb/in <sup>3</sup>	Fiber Density
Filament Diameter	13 Åµm	13 Åµm	
Fiber Count	1.67 dtex	1.50 denier	

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	190 MPa	27600 psi	
Elongation at Break	15 - 27 %	15 - 27 %	
Tenacity	>= 0.140 N/tex	>= 1.59 g/denier	

Descriptive Properties	Value	Comments
Typical Finish Content, %	0.6	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China