

SK Chemicals SKYTHANE® U1753C Ink Binder

Category: Other Engineering Material, Additive/Filler for Polymer, Polymer, Thermoplastic, Elastomer, TPE, Polyurethane, TP

Material Notes:

Description: SK Chemicals has supplied Thermoplastic Polyurethane Elastomer (TPU) under the name of SKYTHANE. Applications include: Keyboard CoversOutsoles of Soccer ShoesWire and CableAirbagsSheets and FilmHoses and TubingShoe ComponentsFire HosesInformation provided by SK Chemicals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SK-Chemicals-SKYTHANE-U1753C-Ink-Binder.php

Physical Properties	Metric	English	Comments
Solids Content	40 %	40 %	ASTM D1259
Viscosity	40000 - 80000 cP	40000 - 80000 cP	ASTM D803
Molecular Weight	60000 g/mol	60000 g/mol	ASTM D3536

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	58.8 MPa	8530 psi	ASTM D638
Elongation at Break	200 %	200 %	ASTM D638
100% Modulus	0.00441 GPa	0.640 ksi	ASTM D638

Thermal Properties	Metric	English	Comments
Glass Transition Temp, Tg	5.00 °C	41.0 °F	ASTM E1356

Descriptive Properties	Value	Comments
Appearance	Pale Yellow Liquid	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China