

SMAC CABLEÂ® 2514S-20-10 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2514S-20-10-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	18.8 daN	11.0 mm, 45Â° down and out
	32.0 daN	8.8 mm, down
	33.5 daN	4.1 mm, up
	34.5 daN	8.2 mm, up and down
	34.5 daN	8.7 mm, left and right
F, Max Static	10.0 daN	1.8 mm, down
	10.0 daN	1.3 mm, up
	10.0 daN	2.6 mm, 45Â° down and out
	5.0 daN	2.0 mm, up and down
	5.0 daN	2.2 mm, left and right
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China