

SMAC CABLEÂ® 2515S-40-10 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2515S-40-10-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	111.0 daN	11.0 mm, up
	25.0 daN	36.0 mm, 45Â° down and out
	34.0 daN	22.0 mm, left and right
	41.5 daN	24.0 mm, down
	42.0 daN	24.4 mm, up and down
F, Max Static	10.5 daN	7.5 mm, 45Â° down and out
	13.8 daN	4.3 mm, down
	13.8 daN	3.0 mm, up
	7.0 daN	6.4 mm, up and down
	7.0 daN	8.5 mm, left and right
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China