

SMAC CABLE® 2516S-10-10 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2516S-10-10-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 °C	356 - 572 °F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	50.0 daN	11.3 mm, 45° down and out
	57.0 daN	8.1 mm, left and right
	59.0 daN	2.6 mm, up
	70.0 daN	8.2 mm, up and down
	78.5 daN	8.3 mm, down
F, Max Static	12.5 daN	2.2 mm, up and down
	12.5 daN	2.5 mm, left and right
	20.0 daN	2.2 mm, 45° down and out
	25.0 daN	1.8 mm, down
	25.0 daN	1.2 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China