

SMAC CABLE[®] 2516S-20-10 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE[®] wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Clips: Stainless steel Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2516S-20-10-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	31.5 daN	17.0 mm, 45Â° down and out
	45.0 daN	4.8 mm, up
	57.0 daN	13.7 mm, down
	62.0 daN	15.0 mm, left and right
	68.0 daN	16.0 mm, up and down
F, Max Static	11.0 daN	4.1 mm, up and down
	11.0 daN	5.0 mm, left and right
	12.5 daN	3.0 mm, 45Â° down and out
	20.0 daN	3.0 mm, down
	20.0 daN	2.8 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China