

SMAC CABLEÂ® 2518S-60-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2518S-60-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	255.0 daN	40.0 mm, up
	44.5 daN	72.0 mm, 45Â° down and out
	70.0 daN	48.0 mm, down
	78.5 daN	60.0 mm, left and right
	90.0 daN	63.2 mm, up and down
F, Max Static	11.8 daN	15.1 mm, up and down
	11.8 daN	16.8 mm, left and right
	17.5 daN	15.5 mm, 45Â° down and out
	23.5 daN	9.0 mm, down
	23.5 daN	8.5 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China