

SMAC CABLEÂ® 2519S-10-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2519S-10-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1450 daN	12.0 mm, up
	275.0 daN	25.0 mm, 45Â° down and out
	444.0 daN	17.0 mm, down
	518.0 daN	20.0 mm, left and right
	535.0 daN	14.3 mm, up and down
F, Max Static	100.0 daN	5.0 mm, 45Â° down and out
	148.0 daN	3.0 mm, down
	148.0 daN	2.5 mm, up
	74.0 daN	5.0 mm, up and down
	74.0 daN	6.0 mm, left and right
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China