

SMAC CABLEÂ® 2519S-30-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2519S-30-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	185.0 daN	41.0 mm, 45Â° down and out
	300.0 daN	27.0 mm, down
	323.0 daN	30.0 mm, left and right
	347.0 daN	26.4 mm, up and down
	981.0 daN	20.0 mm, up
F, Max Static	100.0 daN	5.0 mm, down
	100.0 daN	4.2 mm, up
	50.0 daN	8.1 mm, up and down
	50.0 daN	9.5 mm, left and right
	75.0 daN	8.2 mm, 45Â° down and out
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China