

SMAC CABLEÂ® 2519S-40-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2519S-40-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	150.0 daN	47.0 mm, 45Â° down and out
	240.0 daN	30.0 mm, down
	273.0 daN	37.0 mm, left and right
	291.0 daN	33.6 mm, up and down
	850.0 daN	25.0 mm, up
F, Max Static	40.0 daN	9.3 mm, up and down
	40.0 daN	10.8 mm, left and right
	60.0 daN	9.5 mm, 45Â° down and out
	80.0 daN	5.8 mm, down
	80.0 daN	5.2 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China