

SMAC CABLEÂ® 2519S-60-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloyClips: Stainless steelThreaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2519S-60-08-Damping-Material.php

| Thermal Properties | Metric | English | Comments |
|----------------------------------|---------------|---------------|----------|
| Maximum Service Temperature, Air | 180 - 300 Â°C | 356 - 572 Â°F | |

| Descriptive Properties | Value | Comments |
|-------------------------------|-----------|----------------------------|
| Damping Factor | 0.1 - 0.2 | |
| F, Max Dynamic | 150.0 daN | 48.0 mm, down |
| | 165.0 daN | 58.0 mm, left and right |
| | 187.0 daN | 56.3 mm, up and down |
| | 542.0 daN | 40.0 mm, up |
| | 95.0 daN | 72.0 mm, 45Â° down and out |
| F, Max Static | 25.0 daN | 2.2 mm, up and down |
| | 25.0 daN | 2.9 mm, left and right |
| | 37.5 daN | 15.5 mm, 45Â° down and out |
| | 50.0 daN | 9.0 mm, down |
| | 50.0 daN | 8.2 mm, up |
| Transmissibility at resonance | 3 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China