

SMAC CABLE® 2521S-10-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2521S-10-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	2430 daN	20.0 mm, up
	530.0 daN	55.0 mm, 45Â° down and out
	760.0 daN	35.0 mm, left and right
	820.0 daN	28.4 mm, up and down
	880.0 daN	37.0 mm, down
F, Max Static	148.0 daN	9.1 mm, up and down
	148.0 daN	13.0 mm, left and right
	220.0 daN	11.5 mm, 45Â° down and out
	295.0 daN	7.0 mm, down
	295.0 daN	5.0 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China