

SMAC CABLE® 2521S-60-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2521S-60-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	215.0 daN	140.0 mm, 45Â° down and out
	272.0 daN	80.0 mm, left and right
	290.0 daN	78.2 mm, up and down
	362.0 daN	90.0 mm, down
	955 daN	40.0 mm, up
F, Max Static	120.0 daN	11.0 mm, down
	120.0 daN	11.0 mm, up
	61.0 daN	30.1 mm, up and down
	61.0 daN	32.0 mm, left and right
	90.0 daN	30.0 mm, 45Â° down and out
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China