

SMAC CABLEÂ® 25235-20-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-25235-20-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1020 daN	50.0 mm, 45Â° down and out
	2125 daN	51.0 mm, down
	2875 daN	20.5 mm, up
	550.0 daN	21.7 mm, up and down
	835.0 daN	30.0 mm, left and right
F, Max Static	250.0 daN	8.0 mm, up and down
	250.0 daN	9.3 mm, left and right
	400.0 daN	10.0 mm, 45Â° down and out
	500.0 daN	7.5 mm, down
	500.0 daN	4.5 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China