

## SMAC CABLE® 25235-40-08 Damping Material

Category : Other Engineering Material

**Material Notes:**

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_SMAC-CABLE-25235-40-08-Damping-Material.php](http://www.lookpolymers.com/polymer_SMAC-CABLE-25235-40-08-Damping-Material.php)

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 °C	356 - 572 °F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1262 daN	60.0 mm, down
	1440 daN	70.0 mm, left and right
	1550 daN	78.2 mm, up and down
	4398 daN	48.0 mm, up
	789.0 daN	90.0 mm, 45° down and out
F, Max Static	210.0 daN	19.1 mm, up and down
	210.0 daN	20.5 mm, left and right
	315.0 daN	19.0 mm, 45° down and out
	420.0 daN	11.0 mm, down
	420.0 daN	10.0 mm, up
Transmissibility at resonance	3	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China