

SMAC CABLEÂ® 25235-60-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-25235-60-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1010 daN	103.0 mm, up and down
	3120 daN	62.0 mm, up
	585.0 daN	125.0 mm, 45Â° down and out
	935.0 daN	85.0 mm, down
	965 daN	95.0 mm, left and right
F, Max Static	155.0 daN	27.1 mm, up and down
	155.0 daN	29.0 mm, left and right
	235.0 daN	28.0 mm, 45Â° down and out
	310.0 daN	15.5 mm, down
	310.0 daN	13.5 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China