

SMAC CABLEÂ® 2526S-30-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2Threaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2526S-30-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	18770 daN	52.0 mm, up
	3460 daN	10.0 mm, 45Â° down and out
	5530 daN	70.0 mm, down
	6500 daN	77.0 mm, left and right
	6650 daN	66.0 mm, up and down
F, Max Static	1380 daN	23.0 mm, 45Â° down and out
	1850 daN	13.0 mm, down
	1850 daN	11.0 mm, up
	920.0 daN	22.6 mm, up and down
	920.0 daN	24.0 mm, left and right
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China