

## SMAC SMACMOUNT<sup>®</sup> 1195S Damping Material

Category : Other Engineering Material

**Material Notes:**

Specifications - Shock & vibration insulation for: Embedded electronic Trays & racks systems  
 Advantages: No special tools required  
 High damping isolators  
 Small Size  
 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_SMAC-SMACMOUNT-1195S-Damping-Material.php](http://www.lookpolymers.com/polymer_SMAC-SMACMOUNT-1195S-Damping-Material.php)

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	-30.0 - 80.0 °C	-22.0 - 176 °F	SMACTANE <sup>®</sup>
	-55.0 - 150 °C	-67.0 - 302 °F	SMACSIL <sup>®</sup>

Descriptive Properties	Value	Comments
Frequency	100-140 Hz	
Load	2.2 - 6.6 lbs	
Materials	SMACSIL <sup>®</sup>	
	SMACTANE <sup>®</sup>	
Metal parts	Stainless steel	
Overall size	13 mm	∅, ext.
	27 mm	Height
Transmissibility at resonance	<2.5	SMACTANE <sup>®</sup>
	<4	SMACSIL <sup>®</sup>
Weight	2.5 g	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China