

## SMAC SMACMOUNTÂ® 2528S 02 Damping Material

Category : Other Engineering Material

### Material Notes:

Specifications - Shock & vibration insulation for:Aircraft avionics components & subassembliesMissile electronicsVehicular electronics requiring vibration isolationAdvantages :Bushing style mountCountersunk for lowest installed heightCan be pre-loaded to vary natural frequencyAxial to radial stiffness ratio of approx. 1:1Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_SMAC-SMACMOUNT-2528S-02-Damping-Material.php](http://www.lookpolymers.com/polymer_SMAC-SMACMOUNT-2528S-02-Damping-Material.php)

Descriptive Properties	Value	Comments
Load	0.7 kg	60 Hz
	120 N	5 mm, Static (Radial) deflection
	155 N	8 mm, Static (Radial) deflection
	2.3 kg	23 Hz
	50 N	2 mm, Static (Compression) deflection
	55 N	8 mm, Static (Compression) deflection
	55 N	2 mm, Static (Radial) deflection
	60 N	5 mm, Static (Compression) deflection

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China