

SMAC SMACMOUNTÂ® 2528S 03 Damping Material

Category : Other Engineering Material

Material Notes:

Specifications - Shock & vibration insulation for:Aircraft avionics components & subassembliesMissile electronicsVehicular electronics requiring vibration isolationAdvantages :Bushing style mountCountersunk for lowest installed heightCan be pre-loaded to vary natural frequencyAxial to radial stiffness ratio of approx. 1:1Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-SMACMOUNT-2528S-03-Damping-Material.php

Descriptive Properties	Value	Comments
Load	1 kg	60 Hz
	120 N	5 mm, Static (Compression) deflection
	150 N	8 mm, Static (Compression) deflection
	150 N	5 mm, Static (Radial) deflection
	200 N	8 mm, Static (Radial) deflection
	4 kg	23 Hz
	70 N	2 mm, Static (Compression) deflection
	75 N	2 mm, Static (Radial) deflection

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China