

## **SYNTHOS Koplen® 0207 F Expandable Polystyrene**

Category: Polymer, Thermoplastic, Polystyrene (PS), Expanded Polystyrene (EPS)

## **Material Notes:**

Self-Extinguishing type Koplen®. Processing Method: Pre-expansion of beads by water steam, hot water or hot air. Shaping into thin walled products. Specific Characteristics: Flammability according to CSN EN ISO 11925-2, class E and DIN 4102-B1. Typical Application: Thin walled products with walls under 10mm. Light weight ceramics, light weight wall plaster and concrete mix. False ceilings. Synthos was formerly known as Kaucuk. All information provided by Synthos.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_SYNTHOS-Koplen-0207-F-Expandable-Polystyrene.php

Physical Properties	Metric	English	Comments
Bulk Density	0.0250 g/cc	0.000903 lb/in³	Minimum
	0.0250 - 0.0600 g/cc	0.000903 - 0.00217 lb/in³	Typical
Particle Size	400 - 630 Âμm	400 - 630 Âμm	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China