

## SYNTHOS Koplén® 0207 FR Expandable Polystyrene

Category : Polymer , Thermoplastic , Polystyrene (PS) , Expanded Polystyrene (EPS)

### Material Notes:

Low Pentane Self-Extinguishing type Koplén®. Processing Method: By water steam or hot water, the volume of the beads is increased. Foam-processing to thin-wall moldings. Lower density can be achieved after several preforming operations. Typical Application: Thin walled products with walls under 10mm. Light weight ceramics, light weight wall plaster and concrete mix. False ceilings. Synthos was formerly known as Kaucuk. All information provided by Synthos.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_SYNTHOS-Koplén-0207-FR-Expandable-Polystyrene.php](http://www.lookpolymers.com/polymer_SYNTHOS-Koplén-0207-FR-Expandable-Polystyrene.php)

Physical Properties	Metric	English	Comments
Bulk Density	$\geq 0.0250$ g/cc	$\geq 0.000903$ lb/in <sup>3</sup>	Typical
	0.0350 g/cc	0.00126 lb/in <sup>3</sup>	Minimum
Particle Size	400 - 630 Åµm	400 - 630 Åµm	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China