

SYNTHOS Koplen® 2040 F Expandable Polystyrene

Category : Polymer , Thermoplastic , Polystyrene (PS) , Expanded Polystyrene (EPS)

Material Notes:

Self-Extinguishing type Koplen®. Processing Method: Pre-expansion of beads by water steam, hot water or hot air. Shaping into blocks. Specific Characteristics: Flammability according to CSN EN ISO 11925-2, class E and DIN 4102-B1. Typical Application: Drainage boards. Sound insulation boards. Road base. Filling material. The boards acc CSN EN 13163. Synthos was formerly known as Kaucuk. All information provided by Synthos.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SYNTHOS-Koplen-2040-F-Expandable-Polystyrene.php

Physical Properties	Metric	English	Comments
Bulk Density	0.0180 g/cc	0.000650 lb/in ³	Minimum
	0.0200 - 0.0400 g/cc	0.000723 - 0.00145 lb/in ³	Typical
Particle Size	2200 - 3150 Åµm	2200 - 3150 Åµm	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China