

Saint-Gobain CHRÂ® 2819-5(R) Acrylic Adhesive Zone Tape

Category : Polymer , Adhesive , Tape , Thermoplastic , Acrylic (PMMA)

Material Notes:

Specification Notes: 21CFR177.1550 compliant. All data based on a 0.0047 inch test sample. Information provided by Saint Gobain Performance Products.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Saint-Gobain-CHR-2819-5R-Acrylic-Adhesive-Zone-Tape.php

Mechanical Properties	Metric	English	Comments
Elongation at Break	<= 5.0 %	<= 5.0 %	
Tear Strength	30.7 kN/m	175 pli	Initial Tear Strength

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	177 Â°C	350 Â°F	
Minimum Service Temperature, Air	-28.9 Â°C	-20.0 Â°F	

Descriptive Properties	Value	Comments
Color	Tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China