

Saint-Gobain Chemfab® 3 Porous PTFE-Coated Glass

Category: Ceramic, Glass, Glass Fiber

Material Notes:

Description: Chemfab® Porous Series products are lightweight, highly porous materials commonly used as a release (non-stick) layer for composite curing, molding, and other processes that "off-gas." All data based on a 0.0025 inch test sample. Information provided by Saint Gobain Performance Products.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Saint-Gobain-Chemfab-3-Porous-PTFE-Coated-Glass.php

Physical Properties	Metric	English	Comments
Density	0.961 g/cc	0.0347 lb/in³	

Mechanical Properties	Metric	English	Comments
Tear Strength Test	70	70	Lbs./In. Propagation Tear Strength in fill/transverse direction
	90	90	Lbs./In. for warp/longitudinal Propagation Tear Strength
Tear Strength	8.77 kN/m	50.0 pli	Tensile Strength (Fill)
	12.3 kN/m	70.0 pli	Tensile Strength (Warp)

Descriptive Properties	Value	Comments
Weight (oz/yd^2)	1.8	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China