

## Saint-Gobain Chemfab® N2A PTFE Coated Fiberglass Conveyor Belting

Category : Ceramic , Glass , Glass Fiber

### Material Notes:

**Description:** General Notes on Saint Gobain Belting Products: Saint Gobain Performance Plastics developed its belting materials for applications that require superior release characteristics, permeability for rapid drying, dimensional and thermal stability, and the dynamic strength to stand up to the most rigorous operating conditions. The unique behavior of the materials results in a product that is more practical and cost-effective than conventional belting materials. **Release Properties:** The release characteristics of PTFE are superior to those of any other high-temperature material. This non-stick property is retained over a full range of operating temperatures. **Permeability:** Our belting combines a maximum amount of open area with good mechanical strength. The result is a very high level of controlled air flow through the belt, maximizing the rate of drying. **Dimensional Stability:** The woven reinforcement results in an elongation of approximately 1% under normal mechanical loading, even at temperatures of 550°F. Length distortion is exceptionally low, while width rigidity and stability are enhanced by the high modulus of the reinforcement. **Thermal Stability:** Chemfab® brand belting may be used continuously at temperatures up to 550°F without reducing its performance. **Dynamic Stability:** Our belting has been subjected to static and dynamic tests which indicate that it can withstand all normal operating conditions affecting service life. **Chemical Resistance:** PTFE surfaces are unaffected by most chemicals and solvents. **Notes on N2A PTFE Coated Fiberglass Conveyor Belting:** Chemfab® N2A is a structural-type product modified slightly for industrial applications. It has high strength and high resistance to tearing. The color, which is manufactured as beige, will quickly fade to white when exposed to sunlight. The substrate is fiberglass and the coating material is PTFE (PTFE = polytetrafluoroethylene). Material is non-porous. All data based on a 0.03 inch test sample. Information provided by Saint Gobain Performance Products.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Saint-Gobain-Chemfab-N2A-PTFE-Coated-Fiberglass-Conveyor-Belting.php](http://www.lookpolymers.com/polymer_Saint-Gobain-Chemfab-N2A-PTFE-Coated-Fiberglass-Conveyor-Belting.php)

Physical Properties	Metric	English	Comments
Density	1.6911 g/cc	0.061088 lb/in <sup>3</sup>	

Mechanical Properties	Metric	English	Comments
Elongation at Yield	<= 2.0 %	<= 2.0 %	Value given for Elongation at a loading of 40 lbs/in
Tear Strength Test	50	50	Lbs./In. Propagation Tear Strength in fill/transverse direction
	60	60	Lbs./In. for warp/longitudinal Propagation Tear Strength
Tear Strength	87.7 kN/m	500 pli	Tensile Strength (Fill)
	123 kN/m	700 pli	Tensile Strength (Warp)

Descriptive Properties	Value	Comments
Weight (oz/yd <sup>2</sup> )	38	

## **Contact Songhan Plastic Technology Co.,Ltd.**

**Website : [www.lookpolymers.com](http://www.lookpolymers.com)**

**Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)**

**Tel : +86 021-51131842**

**Mobile : +86 13061808058**

**Skype : lookpolymers**

**Address : United North Road 215,Fengxian District, Shanghai City,China**