Shandong Dongyue Polymer DF-302 PTFE Aqueous Dispersion 60%

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

Material Notes:

Usage: The resin is used for impregnating porous material, such as asbestos, fiberglass, anti-corrosive, abrasion resistant, filature and lubricating materials.Packing: The PTFE is packed in PVC circular barrels.Transportation: The products are transported according to non-dangerous products. Heat, moisture, freezing and strong shock should be avoided during transportation. Over-bumpiness is apt to make the resin settle down.Conformable with Q/DYG 005-2003Information provided by Shandong Dongyue Polymer Material Co., Ltd

Order this product through the following link:

http://www.lookpolymers.com/polymer_Shandong-Dongyue-Polymer-DF-302-PTFE-Aqueous-Dispersion-60.php

Physical Properties	Metric	English	Comments
рН	7.0 - 8.0	7.0 - 8.0	
Viscosity	15 - 30 сР	15 - 30 сР	

Descriptive Properties	Value	Comments
Appearance	Milky or Yellowish liquid	
Content of Case Active Agent (%)	4-6	
For Process	coating and impregnating	
PTFE Content (%)	58-62	

Contact Songhan Plastic Technology Co., Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China