

Sharadaa Ceramics LI SILL-II High Alumina Brick

Category : Ceramic , Oxide , Aluminum Oxide

Material Notes:

Services Offered: Retrofitting of Furnace, Installation of Castables/Bricks/Ceramic Fiber Modules, Castable Laying by Vibrocasting/Guniting, Turnkey Installation Boiler/Chimney/Heater/Reformer/Rotary Kiln, Heat Curing and Acid Proof Lining Industry
Focuses: Steel, Sponge, Rolling Mills, Coke Oven, Ferrous Foundries, Non-Ferrous, Cement, Petro Chemical, Mineral Processing, Sugar / Paper Mills and Chemical Plants
Information provided by Sharadaa Ceramics Pvt. Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sharadaa-Ceramics-LI-SILL-II-High-Alumina-Brick.php

Physical Properties	Metric	English	Comments
Bulk Density	2.35 g/cc	0.0849 lb/in ³	
Porosity	16 - 18 %	16 - 18 %	

Mechanical Properties	Metric	English	Comments
Compressive Strength	44.1 MPa	6400 psi	Cold Crushing

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1500 Â°C	2730 Â°F	

Component Elements Properties	Metric	English	Comments
Al ₂ O ₃	56 - 58 %	56 - 58 %	
Fe ₂ O ₃	1.0 - 1.2 %	1.0 - 1.2 %	

Descriptive Properties	Value	Comments
PCE Orton	36	
Permanent Linear Change	-0.5 - 0.5%	1500Â°C

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China