

Sharadaa Ceramics REFCAST LT Dense Castables

Category: Ceramic

Material Notes:

Description: We offer a range of Dense Castables that are conventional castable and extensively used in boiler work, general furnace and burner blocks. Made as per international standards, our range is known for its high strength, low thermal conductivity and requires less maintenance. Information provided by Sharadaa Ceramics Pvt. Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sharadaa-Ceramics-REFCAST-LT-Dense-Castables.php

Physical Properties	Metric	English	Comments
Bulk Density	>= 1.80 g/cc	>= 0.0650 lb/in³	Sample, cast, cured, dried at 110°C
Grain Size	<= 5000 Âμm	<= 5000 Âμm	

Mechanical Properties	Metric	English	Comments	
Compressive Strength	19.6 MPa	2840 psi		
	@Temperature 800 °C	@Temperature 1470 °F	Cold Crushing	
	24.5 MPa	3560 psi	Cold Crushing	
	@Temperature 110 °C	@Temperature 230 °F	Cold Crushing	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	800 °C	1470 °F	

Component Elements Properties	Metric	English	Comments	
Al203	>= 30 %	>= 30 %		
Fe2O3	<= 5.0 %	<= 5.0 %		

Processing Properties	Metric	English	Comments
Moisture Content	12 - 14 %	12 - 14 %	

Descriptive Properties	Value	Comments
Permanent Linear Change	-1.0 - 1.0%	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com



Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China