

Sharadaa Ceramics REFCAST NORMAL Dense Castables

Category: Ceramic

Material Notes:

Description: We offer a range of Dense Castables that are conventional castable and extensively used in boiler work, general furnace and burner blocks. Made as per international standards, our range is known for its high strength, low thermal conductivity and requires less maintenance. Information provided by Sharadaa Ceramics Pvt. Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sharadaa-Ceramics-REFCAST-NORMAL-Dense-Castables.php

| Physical Properties | Metric | English | Comments |
|---------------------|--------------|------------------|-------------------------------------|
| Bulk Density | >= 2.00 g/cc | >= 0.0723 lb/in³ | Sample, cast, cured, dried at 110°C |
| Grain Size | <= 5000 Âμm | <= 5000 Âμm | |

| Mechanical Properties | Metric | English | Comments | |
|-----------------------|-------------------------|-------------------------|-----------------|--|
| | 24.5 MPa | 3560 psi | | |
| Compressive Strength | @Temperature 1100 °C | @Temperature 2010 °F | Cold Crushing | |
| | 34.3 MPa | 4980 psi | Cold Crushing | |
| | @Temperature 110 °C | @Temperature 230 °F | Cold Grasilling | |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|---------|---------|----------|
| Maximum Service Temperature, Air | 1300 °C | 2370 °F | |

| Component Elements Properties | Metric | English | Comments | |
|-------------------------------|----------|----------|----------|--|
| Al203 | >= 45 % | >= 45 % | | |
| Fe2O3 | <= 5.0 % | <= 5.0 % | | |

| Processing Properties | Metric | English | Comments |
|-----------------------|-----------|-----------|----------|
| Moisture Content | 12 - 14 % | 12 - 14 % | |

| Descriptive Properties | Value | Comments |
|-------------------------|-------------|----------|
| Permanent Linear Change | -1.0 - 1.0% | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com



Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China