

## **Sharadaa Ceramics THERMO PATCH Dense Castables**

Category: Ceramic, Oxide, Aluminum Oxide

## **Material Notes:**

Description: We offer a range of Dense Castables that are conventional castable and extensively used in boiler work, general furnace and burner blocks. Made as per international standards, our range is known for its high strength, low thermal conductivity and requires less maintenance. Information provided by Sharadaa Ceramics Pvt. Ltd.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Sharadaa-Ceramics-THERMO-PATCH-Dense-Castables.php

Physical Properties	Metric	English	Comments
Bulk Density	>= 2.50 g/cc	>= 0.0903 lb/in³	Sample, cast, cured, dried at 110°C
Grain Size	<= 5000 Âμm	<= 5000 Âμm	

Mechanical Properties	Metric	English	Comments
Compressive Strength	39.2 MPa	5690 psi	Cold Crushing
	@Temperature 110 °C	@Temperature 230 °F	Cold Crushing
	58.8 MPa	8530 psi	Cold Crushing
	@Temperature 110 °C	@Temperature 230 °F	Cold Clusting

Thermal Properties	Metric	English	Comments	
Maximum Service Temperature, Air	1400 °C	2550 °F		

Component Elements Properties	Metric	English	Comments	
Al203	>= 60 %	>= 60 %		
Fe2O3	<= 2.0 %	<= 2.0 %		

Processing Properties	Metric	English	Comments
Moisture Content	10 - 12 %	10 - 12 %	

Descriptive Properties	Value	Comments
Permanent Linear Change	-1.0 - 1.0%	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China