

## Shin-Etsu Silicones KE-9510U Silicone Elastomer

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Silicone , Silicone Rubber

### Material Notes:

KE9510 U is one of a series of easy processing, general purpose silicone rubber base with low volatile content. It can be used in a variety of applications requiring finishing by molding, extruding or calendering. Product Features: Rubber contacts. Food packing. Industrial packing. Diaphragms. Information Provided by Shin-Etsu Silicones of America, Inc.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Shin-Etsu-Silicones-KE-9510U-Silicone-Elastomer.php](http://www.lookpolymers.com/polymer_Shin-Etsu-Silicones-KE-9510U-Silicone-Elastomer.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.15 g/cc	1.15 g/cc	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	50	50	
Tensile Strength at Break	8.83 MPa	1280 psi	
Elongation at Break	350 %	350 %	
Tear Strength	12.6 kN/m	72.0 pli	Die B
Compression Set	10 % @Temperature 149 Â°C, Time 79200 sec	10 % @Temperature 300 Â°F, Time 22.0 hour	

Processing Properties	Metric	English	Comments
Cure Time	240 min @Temperature 200 Â°C	4.00 hour @Temperature 392 Â°F	Post

Descriptive Properties	Value	Comments
Cure Agent	DBPH	
Cure Type	Post Cure	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China