

Shuman 603 Black HDPE

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

Material Notes:

High density, injection molding grades, good chemical resistance.Data provided by the manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Shuman-603-Black-HDPE.php

Physical Properties	Metric	English	Comments
Density	>= 0.952 g/cc	>= 0.0344 lb/in ³	ASTM D1505
Melt Flow	2.0 - 3.9 g/10 min	2.0 - 3.9 g/10 min	ASTM D1238
	4.0 - 5.9 g/10 min	4.0 - 5.9 g/10 min	
	6.0 - 9.9 g/10 min	6.0 - 9.9 g/10 min	
	10 - 14.9 g/10 min	10 - 14.9 g/10 min	
	15.0 - 18.0 g/10 min	15.0 - 18.0 g/10 min	

Processing Properties	Metric	English	Comments
Processing Temperature	182 - 210 Å°C	360 - 410 Å°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China