

Sibur 153-10K 1st Grade Polyethylene for Cable Production

Category: Polymer, Thermoplastic, Polyethylene (PE), LDPE, Low Density Polyethylene (LDPE), Wire/Cable Grade

Material Notes:

For application of insulation and protective coverings for wiring and cables by extrusion method.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sibur-153-10K-1st-Grade-Polyethylene-for-Cable-Production.php

Physical Properties	Metric	English	Comments
Melt Index of Compound	0.21 - 0.39 g/10 min	0.21 - 0.39 g/10 min	
Collected Volatile Condensable Material	<= 0.10 %	<= 0.10 %	

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 13.7 MPa	>= 1990 psi	
Elongation at Break	>= 600 %	>= 600 %	

Descriptive Properties	Value	Comments
Flow Limit at Tension	>9.8 MPa	
Number of Inclusions	Non-normalized	
Spread Flow Batch Error	<±12 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China