

Sibur APP-G Atactic Polypropylene

Category: Polymer, Thermoplastic, Polypropylene (PP), Polypropylene, Molded

Material Notes:

For preparation of polymer, bitumen-polymer and polymer-mineral mastics. Individual melts and compositions used for anti-corrosion covers for underground piping, different building structures, structures of industrial equipment, for improvement of mechanical-physical properties of asphalt covering and putty, as well as rubber shoe industry as additions to rubber mixtures.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sibur-APP-G-Atactic-Polypropylene.php

Physical Properties	Metric	English	Comments	
Viscosity Measurement	80 - 5000	80 - 5000	units unknown	
	@Temperature 180 °C	@Temperature 356 °F	units unknown	
Collected Volatile Condensable Material	<= 3.0 %	<= 3.0 %		

Thermal Properties	Metric	English	Comments
Melting Point	100 - 160 °C	212 - 320 °F	

Descriptive Properties	Value	Comments
Mass Share of Isotactic Fraction	<40%	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China