

## Sichuan Deyang Haton® hp23310 Polyphenylene Sulfide Coating

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS) Coating Resin

**Material Notes:**

Powder; anti-corrosion, wear resistant Information provided by Sichuan Deyang Chemical Co., LTD

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Sichuan-Deyang-Haton-hp23310-Polyphenylene-Sulfide-Coating.php](http://www.lookpolymers.com/polymer_Sichuan-Deyang-Haton-hp23310-Polyphenylene-Sulfide-Coating.php)

Physical Properties	Metric	English	Comments
Water Absorption	<= 0.030 %	<= 0.030 %	GB/T 1034-2008

Mechanical Properties	Metric	English	Comments
Impact	NB	NB	Gb1720

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	160 - 220 Â°C	320 - 428 Â°F	

Descriptive Properties	Value	Comments
Chemical Resistance	Ammonia, 40%	< 0.001 mg/h*cm<sup>2</sup>
	Hydrochloric Acid, 40%	< 0.001 mg/h*cm<sup>2</sup>
	Sodium Chloride, 5%	< 0.001 mg/h*cm<sup>2</sup>
	Sodium Hydroxide, 50%	< 0.001 mg/h*cm<sup>2</sup>
	Sulfuric Acid, 40%	< 0.001 mg/h*cm<sup>2</sup>
Pencil Hardness	>2 H	GB/T6739
Wear Resistance, g	= 0.029	GB1768-79

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China