

Sichuan Deyang Haton® hs12370 Polyphenylene Sulfide Coating

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS) Coating Resin

Material Notes:

Suspension; anti-corrosion Information provided by Sichuan Deyang Chemical Co., LTD

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sichuan-Deyang-Haton-hs12370-Polyphenylene-Sulfide-Coating.php

Physical Properties	Metric	English	Comments
Water Absorption	<= 0.020 %	<= 0.020 %	GB/T 1034-2008

Mechanical Properties	Metric	English	Comments
Impact	NB	NB	Gb1720

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	160 - 220 Â°C	320 - 428 Â°F	

Descriptive Properties	Value	Comments
Chemical Resistance	Ammonia, 40%	< 0.001 mg/h*cm²
	Hydrochloric Acid, 40%	< 0.001 mg/h*cm²
	Sodium Chloride, 5%	< 0.001 mg/h*cm²
	Sodium Hydroxide, 50%	< 0.001 mg/h*cm²
	Sulfuric Acid, 40%	< 0.001 mg/h*cm²
Heat Resistance, g	0.18	260Â°C, 500 h
Pencil Hardness	>5 H	GB/T6739

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China