

Silberline Aquavet® 5500nl-136M

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Aquavet® grades are aluminum pigment pellets designed for use in aqueous inks for flexographic and gravure printing. The pellets are composed of 80% aluminum pigment and 20% of a proprietary polymeric dispersant/inhibitor blend. The dispersant/inhibitor blend allow the pigment pellets to disperse directly in water or for faster dispersibility in a water/co-solvent blend. The inhibitor is effective at reducing the aluminum-water reaction in a broad range of waterborne ink resins at higher pH levels. Due to their unique carrier system, Aquavet® pigments can be used in ink systems where block resistance and water spotting resistance are required. High or excessive shear during processing will reduce the effectiveness of the inhibitor and should be avoided. Applications: General Industrial; Printing Inks; Waterborne

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silberline-Aquavet-5500nl-136M.php

Physical Properties	Metric	English	Comments
Specific Gravity	2.00 g/cc	2.00 g/cc	
Volatiles	1.5 %	1.5 %	
Particle Size	14 Åµm	14 Åµm	
Particle Mesh Size	<= 325 Mesh	<= 325 Mesh	0.1% retained

Descriptive Properties	Value	Comments
Aluminum Flake, wt%	80	
Category	Non-leafing	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China