

## Silberline Sparkle Silvex® 795-20-D

Category: Other Engineering Material, Additive/Filler for Polymer

## **Material Notes:**

Sparkle Silvex® D grades are aluminum pigment flakes dampened with a plasticizer to help prevent the individual flakes from becoming airborne during handling and processing. They are well suited for use in liquid colorant applications where processing temperatures are below the volatilization point of the carrier. Sparkle Silvex® D grades are compatible with a variety of resins including vinyl, polyolefins and styrene. Sparkle Silvex® D grades are dampened with diisodecyl phthalate. Sparkle Silvex® D grades can be used in vinyl screen printing ink formulations with good results. In order to maintain optimum aesthetics, Sparkle Silvex® grades should be dispersed properly. Applications: Plastics

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Silberline-Sparkle-Silvex-795-20-D.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.98 g/cc	1.98 g/cc	
Particle Size	35 µm	35 µm	

Thermal Properties	Metric	English	Comments
Flash Point	224 °C	435 °F	

Descriptive Properties	Value	Comments
% Carrier	20	
Carrier	Diisodecylphthalate	

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China