

Silikony Polskie Polimer MV 1.0 Methylvinylsilicone Gum

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

POLIMER MV is the main starting material for production of HTV silicone rubber. Methylvinylsilicone gum should be compounded with crosslinking agents (peroxides), fillers and other additives. Methylvinylsilicone compound can be crosslinked (vulcanized) giving silicone rubber with high mechanical properties (elasticity, compression resistance, tensile strength and tear resistance). The mechanical properties of HTV silicone rubbers can be adjusted at the stage of compound manufacturing by mixing both types of methylvinylsilicone gum in the proper ratio.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silikony-Polskie-Polimer-MV-10-Methylvinylsilicone-Gum.php

Physical Properties	Metric	English	Comments
Solids Content	<= 3.0 %	<= 3.0 %	
Molecular Weight	5.00e+8 - 6.30e+8 g/mol	5.00e+8 - 6.30e+8 g/mol	
Vinyl Acetate Content	0.90 - 1.1 %	0.90 - 1.1 %	
Storage Temperature	0.000 - 30.0 Â°C	32.0 - 86.0 Â°F	

Descriptive Properties	Value	Comments
Color	Colorless	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China