

Silikony Polskie Silpasta A Silicone Paste

Category : Fluid , Lubricant , Silicone Base

Material Notes:

Vaseline consistency, slightly thixotropic Antiadhesive agent used in thermoplastic and thermosetting processing to paste ground joints, rubber gaskets, etc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silikony-Polskie-Silpasta-A-Silicone-Paste.php

Physical Properties	Metric	English	Comments
Density	1.02 - 1.04 g/cc	0.0368 - 0.0376 lb/in ³	
pH	4.0 - 6.0	4.0 - 6.0	
Storage Temperature	-40.0 - 50.0 Â°C	-40.0 - 122 Â°F	

Mechanical Properties	Metric	English	Comments
Penetration	<= 300	<= 300	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	200 Â°C	392 Â°F	
Minimum Service Temperature, Air	-40.0 Â°C	-40.0 Â°F	

Descriptive Properties	Value	Comments
Hygienic Certificate PZH	HK/B/0829/01/2005	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China