

Silikony Polskie Silpasta E Silicone Paste

Category : Fluid , Lubricant , Silicone Base

Material Notes:

Vaseline consistency, thixotropic Electric insulation to paste insulators, conductor connection, cable boxes in environment of high humidity or dustiness.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silikony-Polskie-Silpasta-E-Silicone-Paste.php

Physical Properties	Metric	English	Comments
Density	1.02 - 1.04 g/cc	0.0368 - 0.0376 lb/in ³	
pH	4.0 - 6.0	4.0 - 6.0	
Storage Temperature	-40.0 - 50.0 Å°C	-40.0 - 122 Å°F	

Mechanical Properties	Metric	English	Comments
Penetration	180 - 270	180 - 270	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	200 Å°C	392 Å°F	
Minimum Service Temperature, Air	-40.0 Å°C	-40.0 Å°F	

Electrical Properties	Metric	English	Comments
Volume Resistivity	1.00e+13 ohm-cm	1.00e+13 ohm-cm	
Dielectric Constant	2.9	2.9	
	@Frequency 100 Hz	@Frequency 100 Hz	
Dielectric Strength	30.0 kV/mm	762 kV/in	
Dielectric Loss Index	0.0050	0.0050	
	@Frequency 100 Hz	@Frequency 100 Hz	

Descriptive Properties	Value	Comments
Hygienic Certificate PZH	HK/B/0829/01/2006	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China