

## Silon Tabond 3043 Adhesive Resin

Category : Polymer , Adhesive , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene

### Material Notes:

TABOND 3043 is HDPE modified with maleic anhydride functional groups which promote bonding with different materials like polar polymers, metals and surface treated glass. Characteristics: • Strong adhesion to aminosilane treated glass, Nylon, EVOH, PET, PBT, PC, aluminium, copper, brass and steel • Adhesion durability • Polyolefin like properties and processing Information provided by Silon

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Silon-Tabond-3043-Adhesive-Resin.php](http://www.lookpolymers.com/polymer_Silon-Tabond-3043-Adhesive-Resin.php)

Physical Properties	Metric	English	Comments
Density	0.958 g/cc	0.0346 lb/in <sup>3</sup>	
Melt Flow	1.86 g/10 min @Load 2.16 kg, Temperature 190 °C	1.86 g/10 min @Load 4.76 lb, Temperature 374 °F	

Thermal Properties	Metric	English	Comments
Melting Point	132.2 °C	270.0 °F	DSC

Descriptive Properties	Value	Comments
Color	White	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China