

Silon Tabond 3045 Adhesive Resin

Category : Polymer , Adhesive , Thermoplastic , Polyethylene (PE) , LLDPE , Linear Low Density Polyethylene (LLDPE), Compounding Resin

Material Notes:

TABOND 3045 is LLDPE modified with maleic anhydride functional groups which promote bonding with different materials like polar polymers, metals and surface treated glass. Characteristics: • Strong adhesion to aminosilane treated glass, Nylon, EVOH, PET, PBT, PC, aluminium, copper, brass and steel • Adhesion durability • Polyolefin like properties and processing Information provided by Silon

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silon-Tabond-3045-Adhesive-Resin.php

Physical Properties	Metric	English	Comments
Density	0.914 g/cc	0.0330 lb/in ³	
Melt Flow	1.8 g/10 min @Load 2.16 kg, Temperature 190 °C	1.8 g/10 min @Load 4.76 lb, Temperature 374 °F	

Thermal Properties	Metric	English	Comments
Melting Point	122 °C	252 °F	DSC

Descriptive Properties	Value	Comments
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China