

Silon Tabond 5009 Adhesive Resin

Category : Polymer , Adhesive , Thermoplastic , Polypropylene (PP)

Material Notes:

Tabond 5009 is a chemically modified Polypropylene. This grade is for coextrusion coating of multilayer film to give adhesion between the layers. Characteristics: • Strong adhesion to Aluminium / PP and EVOH / PP • Adhesion durability • Polyolefin like properties and processing • Easy handling during extrusion Information provided by Silon

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silon-Tabond-5009-Adhesive-Resin.php

Physical Properties	Metric	English	Comments
Density	0.905 g/cc	0.0327 lb/in ³	
Melt Flow	32 g/10 min @Load 2.16 kg, Temperature 230 °C	32 g/10 min @Load 4.76 lb, Temperature 446 °F	

Thermal Properties	Metric	English	Comments
Melting Point	143 °C	289 °F	DSC

Descriptive Properties	Value	Comments
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China